

EcoMaster COMMERCIAL

Model s indukčním motorem určený do gastroprovozů



EAN: 8596220000064

58 990 Kč

48 752 Kč bez DPH

To process waste from food preparation and disposal of unconsumed leftovers.

Continuous operations serving up to 2500 meals. Larger hotels, retirement homes, restaurants and hospitals, supermarkets, distilleries, etc.

The COMMERCIAL shredder has a more robust crushing mechanism with a gear ring and a tearing knife beneath the plate, which allows it to handle fibrous and sinewy waste better, such as corn cobs or raw meat.

The upper loading bowl is equipped with water jets that flush the waste and also keep the bowl clean. Due to a separate water supply to the jets and the grinder chamber, it is no longer necessary to let water from the tap flow into the grinder. Using the [electromagnetic valve](#), water is then automatically released when the grinder is turned on.

Our company has products as well as spare parts in stock and provides warranty and post-warranty service and professional installations for households and catering facilities throughout the Czech Republic.

Parameters

Basic parameters

Model:	EcoMaster COMMERCIAL
Use:	Commercial food manufacturing
Commercial use capacity:	Up to 2500 meals
Warranty:	1
Product TARIC code:	Product TARIC code

Technical parameters

Mounting method - installation:	Stand alone (height-adjustable feet), welded under stainless steel bowl. table
Surface finish - color:	Silver varnish
Boot system:	According to installation (pressure switch-button, rocker switch, etc.)
Chamber opening diameter:	15 cm
Bowl Diameter (Stainless Steel Hopper):	45 cm
Rotary plate:	6.4 "with tear notches
Grinding segments:	Tungsten carbide blades with tungsten carbide tips
Grinding ring:	Toothed cast iron, 56 crushing, 8 cutting blades
Bearings:	Maintenance-free, single-row, ball-encapsulated
Protective cushion:	Built-in, rubber with lamellas
Possibility of running:	Continuously
Waste pipe diameter:	A minimum of 50 mm is recommended

Electric specifications

Input voltage:	AC 220-240 V
Frequency:	50/60 Hz
Power input:	2035 W
Performance:	2 HP (1500 W)
Current consumption:	9.25 A
Motor type:	Fan-cooled induction motor
Engine speed:	1450/1725 RPM
Torque:	9.9 Nm
Power cord length:	120 cm
Power cable:	CEE plug 7/7

Protective and security elements

Resettable thermal fuse:	Yes, reset via fuse button
Short circuit protection:	Yes
Electricity class protection:	I. (protective conductor)

Dimensions, weight, packaging

Device dimensions:	820 to 900 x 455 x 455 mm (h / w / d)
Device weight:	52 kg
Packaging dimensions:	870 x 525 x 525 mm (l/w/h)
Packing method:	Wooden box
Width of the packaging:	52,5 cm
Height of the packaging:	87 cm
Depth of the packaging:	52,5 cm

