

Jet Dryer II. JAKOST SMART bílý

VYSTAVENO/ROZBALENO - více informací v popisu



EAN: 8596220006356x

10 990 Kč

9 083 Kč bez DPH

II. Jakost

SMART bílý - SKLADEM 1ks. ROZBALENO, na zadní části přístroje mírně naštípáno, nemá vliv na funkčnost. Obal mírně poškozen. Zažádejte si o podrobnější foto

SMART distinguishes itself from other dryers with the option of advanced settings.

You will appreciate advanced functions and easy operation mainly in corporate restrooms or at home.

Point nozzles for faster drying

The blow dryer SMART has 24 nozzles on each side.

Thanks to the unconventional, pointed shape of the nozzles, the airflow is significantly more concentrated. SMART not only dries but especially wipes the water off hands.

Automatic activation of preheating

SMART evaluates the presence of a person in front of the dryer and switches itself to standby mode.

There will be an automatic turning on of the lighting of the information and control panel and the heating function.

By turning on the heating in advance, warm air blows from the beginning, and you don't have to wait for the dryer to warm up. Drying is then faster and more pleasant.

Jet Dryer SMART automatically heats the air every time the ambient temperature is lower than 20 °C.

Color lighting

The drying zone Jet Dryer SMART is illuminated by colored LED lights. You can choose between blue and red backlighting or leave the lighting completely turned off.

Clear control

The following is the translation of the Czech text to English while preserving the HTML tags: The dryer is equipped with capacitive buttons, and to activate them, you simply need to lightly swipe your finger over them.

In the center of the control panel is a switch that starts the dryer. On the left side, you will find two buttons for switching the fan speed. On the right side, there is a switch for changing the backlight color and heating the air.

Information board

Indicators informing about the current settings of the dryer are placed on the information panel

You can immediately have an overview of the set performance and heating, or the need to replace the HEPA filter or empty the water from the tank.

In the center of the information panel, there is a monochromatic display showing the correct hand-drying procedure.

Two HEPA filters

Two HEPA filters effectively filter the air sucked in by the dryer. The filters are covered with a protective grille.

Simple installation and service

The cover does not need to be removed even when installing the wall dryer. The power supply of the dryer is provided through a standardized power connector (same as for example on a PC).

Dry Floor system

Thanks to Dry Floor, you will always have a dry floor. In the bottom part of the dryer, there is a container for dripping water.

The illuminated red LED diode on the control panel will alert you to a full fuel tank.

ABS plastic

The body of the dryer is made of ABS plastic. It is a very resistant material used in various demanding applications.

Air freshener

Thanks to the integrated gel air freshener, a pleasant scent is released during the operation of the dryer.

Parts of the packaging:

- Assembly instructions
- Assembly suspension panel
- 5 mm anchor 6 pcs
- Power cable
- 4 x 25 mm self-tapping screw 6 pcs

Parameters

Basic parameters

Model:	Jet Dryer SMART
Use:	Corporate toilets, offices, hotels, guest houses and homes
Warranty:	2 years

Technical parameters

Mounting method - installation:	Wall
Noise - sound level:	70 dB
Case material:	ABS plastic
Surface finish - color:	White colored plastic / silver varnish
Antibacterial protection:	Active silver ions
Controls:	Capacitive buttons
Status indication:	LED diodes, display
Drying chamber lighting:	Blue or red LED lighting off
Trigger System (Power On, Control):	Automatic-infrared sensor
Warm air:	YES - according to ambient temperature / permanently on
Air preheating:	Yes - user proximity sensor
Change engine speed / air speed:	Two air speed settings
Air flow:	23.5-29 l / s
Air Speed:	85-105 m / s
Dry Floor system:	Yes - water drip container
Drip tray volume:	670 ml
Number of uses until the drip tray is filled:	730
Operating temperature:	-10 °C / + 40 °C
UV sterilization:	No
Standard air filter:	No
HEPA filter:	Yes
Type:	Sparkling
HEPA filter class:	E12

Electric specifications

Input voltage:	AC 220-240 V
Frequency:	50/60 Hz
Power input:	1800-2000 W
Heating element output:	900 W
Motor power:	900-1100 W
Motor type:	Serial AC commutator
Current consumption:	9A
Standby mode:	<2 W
Power cable:	CEE plug 7/7, IEC-320-C13 connector
Power cord length:	120 cm

Protective and security elements

Protection against excessive use:	Automatic engine shutdown after 25 s
Overcurrent protection, overheating and short-circuit protection:	Yes
Electricity class protection:	I. (protective conductor)
Degree of protection:	IPX4

Dimensions, weight, packaging

Device dimensions:	657x296x203 mm (w/h/d), width of the drying zone opening 75 mm
Device weight:	7.5 kg
Weight including packaging (kg):	9 kg
Packaging dimensions:	730x370x300 mm (h / w / d)
Packing method:	Protective polybag, polystyrene cover, cardboard box
Width of the packaging (cm):	37
Height of packaging (cm):	73
Depth of packaging (cm):	30

