

Jet Dryer II. JAKOST STORM

VYSTAVENO/ROZBALENO - více informací v popisu



EAN: 8596220006394x
2 860 Kč
2 364 Kč excluding VAT



EAN: 8596220006387x
3 290 Kč
2 719 Kč excluding VAT

II. Jakost

Jet Dryer STORM bílý kov - NOVÝ přístroj, bez viditelných známek poškození. Výstavní kus (prezentace, výstavy). Není v originál obalu.

II. Jakost

Jet Dryer STORM stříbrný - přístroj byl zapůjčován na prezentační akce. Oděrky, bez loga. Obal poškozen

STORM represents a combination of compact dimensions of hot air dryers with the drying power of jet air dryers. The robust metal construction is suitable for high-traffic areas. Just install the dryer on the wall and forget about it, no more buying paper towels, no more overflowing trash bins...

The nozzle in the shape of a blade

The warm air comes out of the dryer through a narrow elongated nozzle. This way, water is not only dried, but also wiped off hands. The drying process is similar to that of large jet dryers.

The air is drawn into the dryer from the bottom side of the dryer through the dust filter.

Constant temperature throughout the drying process

You don't have to wait long seconds for the dryer to heat up to full power. The Storm reaches operational temperature practically immediately after inserting your hands.

Easy installation

Installation on the wall is done using four screws. Any service or filter replacement is quick and easy. The rear cover of the dryer just needs to be snapped off, you don't have to unscrew anything.

Antivandal adjustment (in metal adjustment)

The metal cover of the dryer is made from a single piece. A 2-millimeter thick sheet resists any vandalism. The surface finish allows for easy maintenance, the dryer only needs to be wiped with a damp cloth. The cover is resistant to damage from a clumsily discarded cigarette.

Parts of the packaging:

- Assembly instructions
- Allen key
- 5 x 25 mm self-tapping screw, 4 pieces.
- 5 mm anchor 4 pieces.

Parameters

Basic parameters

Model:	JetDryer STORM
Use:	Suitable for all types of operations
Warranty:	3 years

Technical parameters

Mounting method - installation:	Wall
Noise - sound level:	78 dB
Surface finish - color:	White plastic / white lacquer / brushed stainless steel
Controls:	No
Status indication:	No
Boot system:	Automatic- infrared
Trigger distance:	15-20 cm
Warm air:	Yes
Air flow:	23.5 l / s
Air Speed:	85 m / s
UV sterilization:	No
Type:	hot air
Case material:	ABS plastic
Standard air filter:	Yes- filter cartridge

Protective and security elements

Overcurrent protection, overheating and short-circuit protection:	Yes
Electricity class protection:	I. (protective conductor)
Degree of protection:	IP23

Electric specifications

Input voltage:	AC 220-240 V
Frequency:	50/60 Hz
Power input:	1800 W
Heating element output:	1250 W
Motor power:	550 W
Motor type:	Serial AC commutator
Current consumption:	7.8 A
Standby mode:	<2 W
Power cable:	CEE plug 7/7
Power cord length:	90 cm

Dimensions, weight, packaging

Device dimensions:	291x221x152 mm (h / w / d)
Device weight:	ABS white plastic: 3.25 kg / White metal: 3.84 kg / Silver brushed stainless steel: 3.6 kg
Packaging dimensions:	350x270x220 mm (h / w / d)
Weight including packaging (kg):	Matte stainless steel: , White metal:
Packing method:	Protective polybag, polystyrene cover, cardboard box
Width of the packaging (cm):	27
Height of packaging (cm):	35
Depth of packaging (cm):	22

