

Waste King Commercial 1250

Pro střední a větší objem odpadu z přípravy a likvidace zbytků. Provozy s četností nepřesahující ve špičce 2500 jídel.



EAN: 8596220005878

0 Kč

0 Kč bez DPH

Waste King Commercial 1250

For medium and large volumes of waste from food preparation and residue disposal. Facilities serving no more than 2000 meals per hour at peak times.

Parameters

Basic parameters

Model:	Waste King Commercial 1250
Use:	Commercial food manufacturing
Commercial use capacity:	up to 2000
Warranty:	2
Product TARIC code:	85098000

Technical parameters

Mounting method - installation:	Hanging by the throat on the sink flange TM ø 15 cm
Sink flange material:	Stainless steel
Housing material - case:	Polyamide filled with glass
Surface finish - color:	Silver/gray paint
Boot system:	According to installation (pressure switch-button, rocker switch, etc.)
Rotary plate:	Stainless steel
Grinding segments:	Tungsten carbide blades with tungsten carbide tips
Grinding ring:	Refined cast iron
Bearings:	Maintenance-free, ball, enclosed
Protective cushion:	Built-in, rubber with lamellas
Sink drain hole:	Ø 15 cm
Possibility of running:	Continuously
Waste pipe diameter:	A minimum of 50 mm is recommended
Cuff material:	Rubber

Electric specifications

Input voltage:	AC 220-240 V (EU) / 110-120 V (US)
Frequency:	50/60 Hz
Performance:	1 1/4 HP (930W)
Current consumption:	6,6 A
Motor type:	Induction AC motor with self-cooling
Power cable:	NO - (junction box)

Protective and security elements

Resettable thermal fuse:	Yes, reset via fuse button
Short circuit protection:	Yes
Electricity class protection:	I. (protective conductor)

Dimensions, weight, packaging

Device dimensions:	510 x 227 x 227 mm (l/w/h)
Device weight:	23.6 kg
Packaging dimensions:	555x310x310 mm (h/w/d)
Weight including packaging (kg):	26 kg

