

Waste King Commercial 1500

Pro zpracování kuchyňského odpadu z přípravy pokrmů a likvidace zbytků.
Středně velké provozy s četností 3000 jídel.



EAN: 8596220005885

78 990 Kč

65 281 Kč bez DPH

Waste King Commercial 1500 1.5HP single-phase design. For processing kitchen waste from food preparation and disposing of leftovers. Suitable for medium-sized operations with a frequency of 3000 meals. Commercial kitchens, hotels, hospitals, canteens, larger restaurants, food processors.

Parameters

Basic parameters

Model:	Waste King Commercial 1500
Commercial use capacity:	Up to 2000 meals
Warranty:	2
Product TARIC code:	85098000

Technical parameters

Mounting method - installation:	Mounted to the sink's flange Ø 15 cm, mounting system Ø 9 cm
Housing material - case:	Silver varnish
Boot system:	According to installation (pressure switch-button, rocker switch, etc.)
Chamber opening diameter:	Ø 12 cm
Rotary plate:	Stainless steel
Grinding segments:	Tungsten carbide blades with tungsten carbide tips
Grinding ring:	Refined cast iron
Bearings:	Maintenance-free, ball, enclosed
Protective cushion:	Built-in, rubber with lamellas
Possibility of running:	24 hours a day
Waste pipe diameter:	A minimum of 50 mm is recommended
Cuff material:	Rubber

Electric specifications

Input voltage:	230 V
Frequency:	50/60 Hz
Power input:	1 500 W
Performance:	1 1/2 HP (1180 W)
Motor type:	Self-cooled induction motor
Engine speed:	1450/1725 RPM
Torque:	5.88 Nm
Engine power (W):	1500

Protective and security elements

Resettable thermal fuse:	Yes, reset via fuse button
Short circuit protection:	Yes
Electricity class protection:	I. (protective conductor)

Dimensions, weight, packaging

Device dimensions:	510 x227x227 mm (h/w/d)
Device weight:	25 kg
Packaging dimensions:	555x310x310 mm (h/w/d)
Packing method:	Protective polybag, polystyrene cover, cardboard box
Width of the packaging:	31 cm
Height of the packaging:	55.5 cm
Depth of the packaging:	31 cm

