

# Waste King Commercial 500



EAN: 8596220005847

**0 Kč**

0 Kč bez DPH

Waste King Commercial 500

For the disposal of small volumes of waste. Facilities with a frequency not exceeding 250 meals per hour at peak times.

# Parameters

## Basic parameters

Model:	Waste King Commercial 500
Use:	Commercial food manufacturing
Commercial use capacity:	Up to 250 dishes
Warranty:	2
Product TARIC code:	85098000

## Technical parameters

Mounting method - installation:	Mounted to the sink's flange Ø 15 cm, mounting system Ø 9 cm
Sink flange material:	Stainless steel
Housing material - case:	Silver/gray paint
Surface finish - color:	Stainless steel
Boot system:	According to installation (pressure switch-button, rocker switch, etc.)
Rotary plate:	Stainless steel
Grinding segments:	Tungsten carbide blades with tungsten carbide tips
Grinding ring:	Refined cast iron
Bearings:	Maintenance-free, ball, enclosed
Protective cushion:	Built-in, rubber with lamellas
Sink drain hole:	Ø 15.2 cm
Possibility of running:	Continuously
Waste pipe diameter:	A minimum of 50 mm is recommended
Cuff material:	Rubber

## Electric specifications

Input voltage:	AC 220-240 V (EU) / 110-120 V (US)
Frequency:	50/60 Hz
Performance:	1/2HP (370W)
Current consumption:	4.6°C
Motor type:	Induction AC motor with self-cooling
Power cable:	NO - (junction box)
Engine power (W):	370

## Protective and security elements

Resettable thermal fuse:	Yes, reset via fuse button
Short circuit protection:	Yes
Electricity class protection:	I. (protective conductor)

## Dimensions, weight, packaging

Device dimensions:	469 x 227 x 227 mm (w/d/h)
Device weight:	16.8 kg
Weight including packaging (kg):	20

