

Waste King Commercial 750



EAN: 8596220005854

0 Kč

0 Kč bez DPH

Waste King Commercial 750

For the disposal of a lesser volume of food waste. Operations with a frequency not exceeding 400 meals per hour at peak times.

Parameters

Basic parameters

Model:	Waste King Commercial 750
Use:	Commercial food manufacturing
Commercial use capacity:	up to 400
Warranty:	2
Product TARIC code:	85098000

Technical parameters

Mounting method - installation:	Hanging by the throat on the sink flange TM ø 15 cm
Sink flange material:	Stainless steel
Housing material - case:	Polyamide filled with glass
Surface finish - color:	Silver/gray paint
Boot system:	According to installation (pressure switch-button, rocker switch, etc.)
Chamber opening diameter:	Ø 15.2 cm
Rotary plate:	Stainless steel
Grinding segments:	Tungsten carbide blades with tungsten carbide tips
Grinding ring:	Refined cast iron
Bearings:	Maintenance-free, ball, enclosed
Protective cushion:	Built-in, rubber with lamellas
Sink drain hole:	Ø 15 cm
Possibility of running:	Continuously
Waste pipe diameter:	A minimum of 50 mm is recommended
Cuff material:	Rubber

Electric specifications

Input voltage:	AC 220-240 V - 1 phase design
Frequency:	50 / 60 Hz
Performance:	3/4 HP (560W)
Current consumption:	5.3 A
Motor type:	Induction AC motor with self-cooling
Power cable:	NO - (junction box)
Engine power (W):	560

Protective and security elements

Resettable thermal fuse:	Yes, reset via fuse button
Short circuit protection:	Yes
Electricity class protection:	I. (protective conductor)

Dimensions, weight, packaging

Device dimensions:	483 x 227 x 227 mm (h/w/d)
Device weight:	19 kg
Weight including packaging (kg):	25 kg

