## **Waste King Commercial Disposer 1000**

For the normal volume of waste from the preparation and disposal of food scraps. Operations with a frequency not exceeding 1500 meals.

Waste King Commercial 1000 single phase. Suitable for commercial operations with a frequency not exceeding 1500 meals. Schools, hospitals, small and medium-sized restaurants. Wherever there is problematic kitchen waste omanagement, a commercial dipsoser is ideal.



| Product EAN code             | 8596220005861  |
|------------------------------|--|
| Basic parameters             |  |
| Model                        | Waste King Commercial 1000                                       |
| Usage                        | Restaurants, food courts, pubs etc.                              |
| Commercial grinding capacity | up to 1500 meals   |
| Warranty                     | 1 years  |
| Technical parameters         |  |
| Instalation type             | Suspended by the neck on the sink with a flange TM ø 15 cm       |
| Surface treatment - color    | Silvery grey finish  |
| Starting system              | According to installation (pressure switch, rocker switch, etc.) |
| Inlet opening diameter       | Ø 12 cm  |
| Outer gringing ring          | Stainless steel  |
| Grinding components          | Cast iron blades with tungsten carbide blades                    |
| Gringing plate               | Heat-treated cast iron   |
| Bearings                     | Maintenance-free, ball, encapsulated                             |
| Protective splash guard      | Zbuilt-in, rubber with slats                                     |
| Sink opening                 | Ø 15 cm  |
| Possibility of running       | Non-stop 24 h  |
| Waste pipe diameter          | At least 50 mm recommended                                       |
|                              |  |

## **Electrical specification**

| Voltage                      | 110-120 / 220-240 V                                   |
|------------------------------|---|
| Frequency                    | 50/60 Hz  |
| Wattage                      | 1 500 W   |
| Motor power                  | 1 HP (745 W)  |
| Amperes                      | 12 / 6 A  |
| Type of motor                | Induction motor with self-cooling                     |
| RPM                          | 1450 / 1725 rpm                                       |
| Length of the power cable    | 200 cm  |
| Power cable                  | Plug Schuko CEE 7/7                                   |
| Securing and protective elem | ents  |
| Thermal return fuse          | Yes, reset switch                                     |
| Short circuit protection     | Yes   |
| El. Class protection         | I. (protective conductor)                             |
| Dimensions, weight, packagir | ng  |
| Product size                 | 510x227x227 mm (height/width/height)                  |
| Product weight               | 19 kg   |
| Packaging size               | 555x310x310 mm (height/width/height)                  |
| Packaging                    | Protective foil, polystyrene packaging, cardboard box |